

激光测距仪

Laser Distance Meter

SW-GB

项目 ITEMS	参数
测量范围 Measurement Range	50m/70m/100m
测量精度 Accuracy	±(2mm+D*1/10000)
显示屏 Screen	2.2寸黑白屏
角度测量范围 Dip Measuring Range	±90°
角度精度 Angle Accuracy	±1°
激光类型 Laser Type	Class II 500-800nm, <1mW
连续测量 Continuous Measurement	√
面积/体积测量 Area/ Volume Measurement	√
墙面面积测量 Wall area Measurement	√
勾股测量 Pythagorean Measurement	√
测角测高功能 Angle And Height Measurement	√
加减测量功能 Add/Subtract Measurement	√
面积体积加减 Area&Volume Addition Subtraction	√
最大/最小测量 Max/Min Value	√
语音播报 Voice Prompt	√
知户型功能	√
智能蓝牙 APP	√
底座螺纹尺寸	1/4寸铜螺母
自助校准 Self-Calibration	√
存储记录笔数 Max Storage	100笔/Units
自动关闭激光 Auto Laser-off	20s(单次测/Single Measurement)
自动关机 Auto Power-off	150s
电池类型 Battery	3.7V 600mAh 锂电池 Li-ion
USB 充电时长 USB Charging Time	约1.5小时/About 1.5 hours
测距电池工作时间 Measurement Times At Full Charge	单次测量, 语音开≥5000次(满电) /Single measuring 5000 times
存储温湿度 Storage Temperature&Humidity	-20℃~60℃, 10%~90%RH
工作温度 Working Temperature&Humidity	0℃~40℃, 10%~90%RH
机身尺寸 Product Dimension	118x54x26mm



■ 机械卷尺参数

卷尺量程 Measuring Range	2m
卷尺最小刻度 The Minimum Scale	1mm
卷尺单位 Unit	单面公英制 Single-sided imperial system
尺带宽度 Tape Width	9.0mm
尺带厚度 Tape Thickness	0.1mm
尺带材质 Tape Material	65锰钢 (黄底黑字) Manganese Steel
尺带精度 Tape Accuracy	±1mm
尺带水平挺直长度 Tape horizontal straight length	按照QB/T 2443-2011标准 According to QB/T 2443-2011 standard
卷尺自锁功能 Self-Locking	X

