

手持式测距望远镜 LASER RANGEFINDER TELESCOPE SW-E

项目 ITEMS	参数 SPECIFICATIONS		
屏幕显示 Screen	黑显black	红绿显red&green	红黑显red/black
测量范围 Measurement Range	3-700m/1000m/1500m	3-1000m/1500m/2000m	
单位 Unit	m(Meter), Y(Yard)		
测量反应时间 Measuring Time	<0.5s (<100m 0.3s; > 700m 0.45s)		
振动提示 Vibration prompt	√		
磁吸功能 Slope Measurement	√		
直线距离测量 Straight Line Distance Measurement	√		
旗杆锁定 Fagpole Locking	√		
方位角测量 Azimuth Mode	√		
望远镜倍率 Magnification	6X±5%		
视场 Field of View	7.0°±5%		
物镜孔径 Objective Caliber	23.5mm		
目镜孔径 Eyepiece Caliber	15±1mm		
出瞳直径 Exit Pupil Caliber	3.7±0.5mm	4.0±0.5mm	3.9±0.5mm
视度调节范围 Diopter Adjustable Range	± 6°		
激光等级 Laser Class	Class 1, 905nm		
存储温湿度 Storage Temperature/Humidity	-20°C ~ 60°C、20% ~ 80%RH		
测距精度 Measurement Accuracy	1.0m±D*0.3%		
工作温度 Working Temperature	-10°C ~ 50°C		
防护等级 Water Resistant	IP54		
电池类型 Battery	3.7V 750mAh锂电池 Li-ion		
电池工作时间 Battery Working Life	20000次测量(满电) Single measuring 20000 times after one time full charging		
充电规格 Charging Specifications	DC5V 0.5A Type-C		
外形尺寸 Product Dimension	111.5x75.8x43.5mm		
外箱尺寸 Carton MEAS			
装箱数量 QTY per Carton			
重量 G.W per Carton			



深达威科技(广东)股份有限公司

Sndway Technology (Guangdong) co., Ltd.
地址: 东莞市虎门镇虎门团结路58号深达威科技园
Add: Sndway Science & Technology Industrial Park, 58
Tuanjie Road, Humen 523930, Dongguan, China
邮箱/E-mail: market@sndway.com
全国咨询服务热线/Service Hotline: 400-125-6969
网址/Url: www.sndway.com 电话/Tel: 0769-85265688



官网 / WEB



关注公众号