

可燃气体检测仪

COMBUSTIBLE GAS DETECTOR

SW-733GS

项目 ITEMS	参数 SPECIFICATIONS
语言界面 Language Interface	中文/英文 Chinese/English
语音播报 Voice Broadcast	报警音提示 Alarm Reminding
探测气体 Application	天然气(Natural Gas)、石油气(Petroleum Gas) 等可燃气体(Combustible Gas)
量程 Range	0~20%LEL, 0~10000 μ mol/mol (ppm)
分辨率 Resolution	0.1%LEL, 1 μ mol/mol (ppm)
气体浓度单位 Gas Concentration Unit	%LEL、ppm、 μ mol/mol三种单位切换
预热时间(T90) Preheating Time (T90)	30秒 / 30s
响应时间(T90) Response Time (T90)	< 30秒 / 30s
采样方式 Sampling Methods	扩散式 / Diffusion
校正 Correction	用户可零点校准 Zero calibration by the user
运行时间 Operating Time	满电续航约9小时(照明关) Standby time $\approx$ 8h (Lighting off)
显示 Screen	2.4寸彩屏/2.4-in color screen
时间显示 Time display	√
默认可燃气体报警值 Default combustible gas alarm value	底限报警1000 μ mol/mol, 高限报警4000 μ mol/mol, 用户也可自行 设置 / Low concentration alarm: 4000 μ mol/mol, High Concentration Alarm: 4000 μ mol/mol. Users can set it by themselves
报警 Alarm	声音/灯光/振动/屏幕显示四种报警模式, 工作电压欠压指示 Four alarm modes of sound/light/vibration/screen display, undervoltage indication of operating voltage.
音频提示 Alarm audio prompt	浓度到达“下限”或“上限”时, 会产生报警。 When the concentration reaches the "lower limit" or "upper limit", an alarm will be triggered.
防爆标志 Ex-mark	Ex ib IIB T3 GB
电池类型 Battery	3.7V 2000mAh锂电池/ lithium battery
适用温湿度范围 Working Temperature&Humidity	-10°C~50°C; 20%~95%RH
储存温湿度 Working temperature and humidity	-20°C~60°C; $\leq$ 85%RH
外形尺寸 Product Dimension	170x66x28.5mm(万向定型管长约260mm) (length of universal shaping tube is about 260mm)
外箱尺寸 Carton MEAS	
装箱数量 QTY per Carton	
重量 G.W per Carton	

